

---

## Contents

---

<b>Preface</b>	ix
<b>List of Symbols</b>	xi
<b>Introduction</b>	xv
<b>Chapter 1. Background Noise in Electronics</b>	1
1.1. Introduction	1
1.2. Spontaneous fluctuations in electronic components	2
1.2.1. Introduction	2
1.2.2. Thermal noise	2
1.2.3. Shot noise	7
1.2.4. Generation / recombination noise	7
1.2.5. Excess noise	8
1.3. Noise factor	9
1.3.1. Definition	9
1.3.2. Reference temperature for the noise factor	11
1.3.3. Importance of the noise factor in telecommunications	12
1.4. Noise in two-ports	13
1.4.1. Representation of noise in two-ports	13
1.4.2. Expression of the noise factor of a two-port	15
1.4.3. Minimum noise factor of a two-port	16
1.4.4. Inverse relations	19
1.5. Characterization of noise in a two-port	20
1.6. Conclusion	22
<b>Chapter 2. Friis Formula</b>	23
2.1. Introduction	23
2.2. Calculation method	24

2.3. Calculation of the admittance parameters of the Q1, Q2 association in cascade . . . . .	26
2.4. Contribution of noise generators $e_1$ , $i_1$ , $e_2$ and $i_2$ to $I_1$ and $I_4$ . . . . .	27
2.4.1. Introduction . . . . .	27
2.4.2. Contribution of the noise generator $e_1$ . . . . .	27
2.4.3. Contribution of the noise generator $i_1$ . . . . .	28
2.4.4. Contribution of the noise generator $e_2$ . . . . .	28
2.4.5. Contribution of the noise generator $i_2$ . . . . .	29
2.5. $e_{Tot}$ and $i_{Tot}$ identification . . . . .	30
2.6. Calculation of $F_{12}(YS)$ . . . . .	30
2.7. Friis Formula . . . . .	31
2.7.1. Introduction . . . . .	31
2.7.2. Transducer power gain . . . . .	32
2.7.3. Available power gain . . . . .	34
2.8. Conclusion . . . . .	35
<b>Chapter 3. Adapted Attenuator and Noise Factor</b> . . . . .	37
3.1. Introduction . . . . .	37
3.2. Calculation of Y and S parameters . . . . .	38
3.3. General representation of noise in two-ports . . . . .	39
3.4. Equivalent noise generators at the input of the adapted attenuator . . . . .	40
3.5. Noise factor on $50 \Omega$ of the adapted attenuator . . . . .	41
3.6. Using Bosma's theorem . . . . .	43
3.7. Consequences on the structure of a receiver . . . . .	46
3.8. Equivalent noise resistance and noise conductance at the input . . . . .	47
3.9. Conclusion . . . . .	48
<b>Chapter 4. Noise Factor Measurement on <math>50 \Omega</math></b> . . . . .	51
4.1. Introduction . . . . .	51
4.2. Noise factor measurement by Y factor . . . . .	52
4.3. Second stage correction . . . . .	54
4.4. Measurement procedure and calculation of the noise factor of the DUT	55
4.5. Available power gain and insertion power gain of the DUT . . . . .	57
4.6. Sample results . . . . .	60
4.7. Conclusion . . . . .	62
<b>Chapter 5. Characterization in Noise</b> . . . . .	65
5.1. Introduction . . . . .	65
5.2. The tuner . . . . .	67
5.2.1. Tuner constitution . . . . .	67
5.2.2. Noise behavior of the noise diode + tuner assembly . . . . .	68
5.2.3. Tuner calibration procedure . . . . .	71

5.3. Characterization in noise of the noise measurement chain . . . . .	73
5.4. Characterization in $S$ parameters of the device under test. . . . .	74
5.5. Noise characterization of the device under test. . . . .	74
5.6. Validation of a noise characterization bench . . . . .	75
5.6.1. Introduction . . . . .	75
5.6.2. 2.5 dB adapted attenuator . . . . .	76
5.6.3. Coaxial cable . . . . .	78
5.7. Conclusion . . . . .	79
<b>Chapter 6. Exercises and Answers</b> . . . . .	81
6.1. Exercises . . . . .	81
6.2. Solutions . . . . .	91
<b>Conclusion</b> . . . . .	117
<b>Appendix 1</b> . . . . .	119
<b>Appendix 2</b> . . . . .	125
<b>Appendix 3</b> . . . . .	135
<b>Appendix 4</b> . . . . .	149
<b>Bibliography</b> . . . . .	163
<b>Index</b> . . . . .	165