

Table of Contents

| | |
|---|----|
| Chapter 1. Introduction | 1 |
| 1.1. Why a network? | 1 |
| 1.2. Network classification | 2 |
| 1.2.1. Function of distance | 3 |
| 1.2.2. Function of the topology. | 6 |
| 1.3. Interconnection networks. | 8 |
| 1.4. Examples of network utilization | 10 |
| 1.5. The Internet network | 11 |
| 1.5.1. History | 12 |
| 1.5.2. Functioning principle | 13 |
| 1.6. Structure of this book | 15 |
| | |
| Chapter 2. Standardization and Wiring | 19 |
| 2.1. The IEEE 802 committee. | 19 |
| 2.1.1. Traffic types and constraints | 19 |
| 2.1.2. Constraints | 20 |
| 2.2. The standards. | 21 |
| 2.3. IEEE 802.1 addressing | 27 |
| 2.3.1. MAC address | 29 |
| 2.3.2. EUI-64 | 30 |
| 2.4. Cabling rules | 30 |
| 2.4.1. Twisted pair wiring. | 31 |
| 2.4.2. Optical fibers | 34 |
| | |
| Chapter 3. Ethernet and IEEE 802.3 Protocols | 37 |
| 3.1. History. | 37 |
| 3.2. Physical level. | 39 |
| 3.2.1. The supports | 39 |
| 3.2.2. The interfaces and connectors | 43 |

| | |
|--|-----------|
| 3.3. The fundamentals of CSMA/CD | 45 |
| 3.3.1. Protocol parameters | 47 |
| 3.3.2. BEB algorithm | 48 |
| 3.3.3. Limits of the CSMA/CD algorithm | 52 |
| 3.3.4. The repeaters | 52 |
| 3.4. Frame format | 53 |
| 3.4.1. Physical level | 53 |
| 3.4.2. MAC level | 54 |
| 3.5. The 10BASE5 network | 58 |
| 3.5.1. The equipment | 58 |
| 3.5.2. Manchester coding | 60 |
| 3.6. Devices for the 10BASE2 | 62 |
| 3.7. Twisted pair equipment | 63 |
| 3.7.1. The hubs | 64 |
| 3.7.2. The switches | 64 |
| 3.7.3. The 100BASE-T | 68 |
| 3.7.4. 1000BASE-T | 76 |
| 3.7.5. Auto-negotiation | 77 |
| 3.8. Fiber optics | 79 |
| 3.8.1. 10BASE-F | 79 |
| 3.8.2. 100BASE-FX | 80 |
| 3.8.3. 1000BASE-X | 81 |
| 3.8.4. Encoding | 82 |
| 3.8.5. Auto-negotiation | 84 |
| 3.8.6. Half-duplex mode and burst transmission | 86 |
| 3.9. Examples of Ethernet frames | 87 |
| 3.9.1. Signalovera 10BASE2 segment | 87 |
| 3.9.2. Frames | 90 |
| 3.10 Evolution of the Ethernet | 92 |
| Chapter 4. The LLC and SNAP Sublayers | 95 |
| 4.1. Definition | 95 |
| 4.2. LLC frames | 97 |
| 4.2.1. Frame formats | 97 |
| 4.2.2. Examples of protocols | 102 |
| 4.2.3. Window widths | 106 |
| 4.3. Example | 106 |
| 4.3.1. Type 1 LLC | 107 |
| 4.3.2. Type 2 LLC | 107 |
| 4.4. The SNAP layer | 111 |
| 4.4.1. Frame formats | 111 |
| 4.4.2. Example | 112 |

| | |
|---|-----|
| Chapter 5. Interconnection by Bridges: The Spanning Tree Algorithm . . | 115 |
| 5.1. Introduction. | 115 |
| 5.2. Transparent filtering bridges. | 116 |
| 5.2.1. Simple case | 116 |
| 5.2.2. Complex case | 117 |
| 5.3. Spanning tree algorithm | 118 |
| 5.3.1. Example | 121 |
| 5.3.2. Information update | 125 |
| 5.3.3. State diagram | 125 |
| 5.3.4. Message format | 126 |
| 5.3.5. Example | 128 |
| | |
| Chapter 6. Internet | 131 |
| 6.1. The Internet players | 131 |
| 6.1.1. The Internet Society | 132 |
| 6.1.2. The IAB | 132 |
| 6.1.3. The IESG. | 133 |
| 6.1.4. The IRSG | 138 |
| 6.1.5. Address and protocol parameter management | 139 |
| | |
| Chapter 7. IP Protocols | 143 |
| 7.1. Implementation of the TCP/IP protocols. | 143 |
| 7.1.1. Terminal equipment | 145 |
| 7.1.2. Routers | 147 |
| 7.1.3. IP layer architecture | 147 |
| 7.2. Internet addressing | 149 |
| 7.2.1. Notation | 151 |
| 7.2.2. Special IPv4 addresses. | 153 |
| 7.2.3. IPv4 class addressing. | 153 |
| 7.2.4. Hierarchical addressing | 157 |
| 7.2.5. Special IPv4 prefixes and addresses | 166 |
| 7.2.6. Special IPv6 addresses and prefixes | 167 |
| 7.3. The IPv4 protocol (RFC 791, RFC 1122) | 168 |
| 7.3.1. Format of IPv4 datagrams. | 168 |
| 7.4. The ICMP (Internet Control Message Protocol) (RFC 792) | 180 |
| 7.4.1. The message cannot reach its destination. | 183 |
| 7.4.2. Expired TTL and the traceroute program | 183 |
| 7.4.3. Quench source. | 189 |
| 7.4.4. Redirection indication | 189 |
| 7.4.5. Echo/the ping command. | 191 |
| 7.4.6. Netmask request /reply to netmask (RFC 950). | 194 |
| 7.4.7. Information about routers (RFC 1256) | 195 |
| 7.4.8. MTU discovery (RFC 1191) | 195 |

| | |
|--|------------|
| 7.5. The IPv6 protocol | 196 |
| 7.5.1. Format of IPv6 datagrams | 196 |
| 7.5.2. The ICMPv6 protocol | 197 |
| 7.6. Tunnels | 199 |
| 7.6.1. Architecture | 199 |
| 7.6.2. Encapsulations | 200 |
| 7.7. Configurations | 202 |
| 7.7.1. Configuration of a Unix station. | 202 |
| 7.7.2. Visualization. | 202 |
| 7.7.3. Configuration | 204 |
| 7.8. Configuration of a Cisco router | 204 |
| 7.8.1. Visualization. | 205 |
| 7.8.2. Configuration | 205 |
| 7.9. IPv4 and multicast. | 207 |
| 7.9.1. Format of multicast addresses | 208 |
| 7.9.2. The IGMPv2 protocol (RFC 3376) | 210 |
| Chapter 8. Level 4 Protocols: TCP, UDP and SCTP | 213 |
| 8.1. Port notion | 213 |
| 8.2. TCP (Transmission Control Protocol) (RFC 793) | 215 |
| 8.2.1. TCP format message | 216 |
| 8.3. The three protocol phases | 218 |
| 8.3.1. Establishing a connection | 218 |
| 8.3.2. Data transfer | 222 |
| 8.3.3. Closing a connection | 226 |
| 8.4. The options | 227 |
| 8.5. Adaptation to the environment | 230 |
| 8.5.1. Timer management | 230 |
| 8.5.2. Limitations of packets emitted | 236 |
| 8.6. TCP flow control | 239 |
| 8.6.1. Applicative flow control. | 239 |
| 8.6.2. Congestion control at network level | 243 |
| 8.7. Study of TCP by simulations | 252 |
| 8.7.1. Self-clocking | 253 |
| 8.7.2. TCP Tahoe. | 256 |
| 8.7.3. TCP Reno | 258 |
| 8.7.4. TCP newReno | 261 |
| 8.7.5. Selective acknowledgements | 262 |
| 8.8. Network consideration of TCP | 263 |
| 8.8.1. RED. | 263 |
| 8.8.2. Explicit congestion notification (ECN) | 270 |
| 8.8.3. TCP over different supports. | 271 |
| 8.9. The UDP (user datagram protocol) (RFC 768) | 275 |

| | |
|--|------------|
| 8.9.1. Message format | 276 |
| 8.9.2. TCP friendly | 277 |
| 8.9.3. The UDP-Lite protocol (RFC 3828) | 279 |
| 8.9.4. The RTP protocol (RFC 1889) | 280 |
| 8.10. SCTP | 283 |
| 8.10.1. General message format | 284 |
| 8.10.2. Creation of associations | 287 |
| 8.10.3. Data transfer | 291 |
| 8.10.4. Verification of the feasibility of association | 294 |
| 8.10.5. Closing an association | 295 |
| 8.10.6. Example of SCTP traffic | 296 |
| Chapter 9. Address Resolution and Automatic Configuration Protocols . . | 299 |
| 9.1. Introduction | 299 |
| 9.2. The address resolution protocol (ARP) | 300 |
| 9.2.1. ARP frame format | 301 |
| 9.2.2. The cases of broadcast and multicast addresses | 307 |
| 9.3. Neighbor discovery in IPv6 | 308 |
| 9.3.1. Principle | 308 |
| 9.3.2. Example | 309 |
| 9.4. Initialization and auto-configuration | 309 |
| 9.4.1. TFTP (trivial file transfer protocol) (RFC 1350) | 309 |
| 9.4.2. RARP (reverse address resolution protocol) (RFC 903) | 311 |
| 9.4.3. BOOTP (RFC 951 and RFC 1542) | 314 |
| 9.4.4. DHCP (dynamic host configuration protocol) (RFC 2131) | 326 |
| 9.5. The domain name server (DNS) (RFC 1034, RFC 1035) | 333 |
| 9.5.1. General principles | 333 |
| 9.5.2. The principle of interrogation | 337 |
| 9.5.3. .arpa domain | 347 |
| 9.5.4. Protocol | 352 |
| 9.5.5. Server configuration | 363 |
| Chapter 10. Routing Protocols | 367 |
| 10.1. Routing tables | 367 |
| 10.2. Equipment classification | 368 |
| 10.3. Routing table configuration | 369 |
| 10.3.1. Display of the routing table under Unix or Windows | 369 |
| 10.3.2. Display of the routing table under Cisco | 370 |
| 10.3.3. Modification of the routing table under Unix | 372 |
| 10.3.4. Modification of the routing table for Cisco | 372 |
| 10.4. Station or router? | 373 |
| 10.5. High-speed router | 374 |
| 10.6. Router classification | 375 |

| | |
|---|------------|
| 10.7. Routing protocols | 376 |
| 10.8. Autonomous systems | 376 |
| Chapter 11. Internal Routing Protocols | 381 |
| 11.1. The <i>Distant Vector</i> algorithm | 381 |
| 11.1.1. Description | 381 |
| 11.1.2. Convergence problem | 384 |
| 11.1.3. Routing information protocol (RIP) (RFC 1058) | 386 |
| 11.1.4. RIP-2 (RFC 1723). | 390 |
| 11.1.5. Simple authentication. | 392 |
| 11.2. <i>Link State</i> algorithm | 396 |
| 11.2.1. Principles | 396 |
| 11.3. The OSPF protocol | 403 |
| 11.3.1. Vocabulary and concepts | 403 |
| 11.3.2. OSPF protocols (RFC 2328) | 410 |
| 11.3.3. Examples | 420 |
| 11.4. IS-IS | 434 |
| 11.4.1. NSAP and NET addresses | 436 |
| 11.4.2. IS-IS protocols | 439 |
| 11.4.3. Example. | 448 |
| Chapter 12. External Routing Protocols | 453 |
| 12.1. Path announcing | 453 |
| 12.1.1. Principles | 453 |
| 12.1.2. The RIPE database | 458 |
| 12.1.3. Crossing ASs. | 460 |
| 12.2. The interconnection points | 461 |
| 12.3. The symmetry of routes. | 461 |
| 12.4. BGP (border gateway protocol) | 462 |
| 12.4.1. Message format | 463 |
| 12.4.2. Internal BGP | 469 |
| 12.4.3. Use of attributes | 473 |
| 12.4.4. Synchronization between IGP and EGP. | 479 |
| 12.5. Route selection rules. | 480 |
| 12.6. BGP traffic analysis | 481 |
| 12.6.1. IPMA (Internet Performance Measurement and Analysis) project | 482 |
| 12.6.2. Network probe daemon. | 484 |
| 12.7. Reduction of oscillations | 485 |
| 12.8. Routing limit in the Internet | 486 |
| Chapter 13. Virtual Local Networks | 487 |
| 13.1. Definition | 487 |

| | |
|--|------------|
| 13.2. Multicast data management | 488 |
| 13.2.1. GARP (Generic Attribute Registration Protocol) | 490 |
| 13.2.2. GMRP (GARP Multicast Registration Protocol). | 495 |
| 13.3. Virtual networks | 497 |
| 13.3.1. VLAN membership | 499 |
| 13.3.2. Configuration of devices | 500 |
| 13.3.3. Labeling frames | 503 |
| Chapter 14. MPLS (Multi Protocol Label Switching) | 507 |
| 14.1. Routing protocols' limits | 507 |
| 14.2. MPLS header format | 510 |
| 14.3. Principles of operation | 513 |
| 14.4. MPLS label D distribution protocols | 518 |
| 14.4.1. LDP (Label Distribution Protocol) (RFC 5036) | 519 |
| 14.5. Traffic engineering. | 525 |
| Chapter 15. IP on Point-to-Point Links: PPP | 529 |
| 15.1. Serial links | 530 |
| 15.2. SLIP (Serial Link IP, RFC 1055) | 533 |
| 15.2.1. Principle | 533 |
| 15.3. PPP (point-to-point protocol, RFC 1661) | 535 |
| 15.3.1. Adaptation to physical support | 537 |
| 15.3.2. The PPP frames | 539 |
| 15.3.3. Negotiation parameters. | 541 |
| 15.3.4. The LCP protocol | 544 |
| 15.3.5. The authentication protocols (RFC 1334). | 544 |
| 15.3.6. Layer 3 configuration protocols. | 547 |
| 15.3.7. TCP/IP (RFC 1144) header compression | 549 |
| 15.4. Configuration of routers. | 560 |
| 15.5. The RADIUS protocol | 560 |
| 15.6. PPP over X.25 (RFC 1598). | 561 |
| 15.7. PPP over high-speed networks. | 561 |
| 15.8. Bridging with PPP (RFC 1638) | 561 |
| 15.8.1. Data frames. | 562 |
| 15.8.2. Spanning Tree frames | 564 |
| 15.8.3. BCP configuration protocol | 564 |
| 15.9. ADSL network architecture | 565 |
| 15.9.1. PPPoE (PPP over Ethernet) | 566 |
| 15.9.2. L2TP (Layer 2 Tunneling Protocol) | 569 |
| Chapter 16. Network Administration | 571 |
| 16.1. Vocabulary and concepts | 571 |
| 16.1.1. Versions of SNMP | 572 |

| | |
|---|-----|
| 16.2. ASN.1 (Abstract Syntax Notation) | 574 |
| 16.2.1. The standard | 574 |
| 16.2.2. BER (basic encoding rules) encoding | 576 |
| 16.3. Definition of the MIB SNMP (RFC 1213). | 579 |
| 16.4. Format of SNMPv1 messages (RFC 1157). | 581 |
| 16.4.1. Interrogation message | 583 |
| 16.4.2. Management of tables | 584 |
| 16.4.3. Interrogation of MIB | 585 |
| 16.4.4. The trap message | 586 |
| 16.5. Formats of SNMPv2 messages (RFC 1905). | 587 |
| 16.5.1. Primitive getbulk | 587 |
| 16.5.2. Example of getbulk usage | 588 |
| 16.5.3. Error messages. | 588 |
| 16.5.4. Trap messages | 590 |
| 16.6. Examples of SNMPv1 traffic | 590 |
| 16.6.1. Simple interrogation | 590 |
| 16.6.2. Interface requests | 592 |
| 16.7. MIB example | 594 |
| 16.7.1. The <code>system</code> group (1.3.6.1.2.1.1). | 594 |
| 16.7.2. The <code>interface</code> group (1.3.6.1.2.1.2). | 595 |
| 16.7.3. The <code>at</code> group (1.3.6.1.2.1.3) | 598 |
| 16.7.4. The <code>IP</code> group (1.3.6.1.2.1.4) | 599 |
| 16.7.5. The <code>ICMP</code> group (1.3.6.1.2.1.5). | 599 |
| 16.7.6. The <code>TCP</code> group (1.3.6.1.2.1.6) | 599 |
| 16.7.7. The <code>UDP</code> group (1.3.6.1.2.1.7) | 605 |
| 16.7.8. The <code>SNMP</code> group (1.3.6.1.2.1.11). | 607 |
| 16.8. Other MIBs | 607 |
| 16.8.1. The host MIB (RFC 2790). | 608 |
| 16.8.2. The RMON MIB (RFC 1757). | 610 |
| Chapter 17. Security | 613 |
| 17.1. Risks | 613 |
| 17.2. Filtering routers | 614 |
| 17.2.1. IP spoofing | 620 |
| 17.3. Bastion. | 622 |
| 17.4. Proxy | 623 |
| 17.5. NAT (Network Address Translator, RFC 1631) | 624 |
| Chapter 18. Flow Management | 627 |
| 18.1. Quality of service | 627 |
| 18.2. Flow notion | 630 |
| 18.3. Flow management | 631 |
| 18.3.1. Equity | 631 |

| | |
|--|-----|
| 18.3.2. Multiple queue mechanisms | 633 |
| 18.3.3. Single queue mechanisms | 636 |
| 18.3.4. Hierarchical sharing of bandwidth | 640 |
| 18.4. Flow measurements | 644 |
| 18.4.1. Token bucket. | 645 |
| 18.4.2. Shapers | 646 |
| 18.4.3. Network calculus | 646 |
| 18.5. Integration of services on the Internet | 648 |
| 18.5.1. RSVP characteristics | 649 |
| 18.5.2. Elements of particular networks | 653 |
| 18.5.3. RSVP message format | 653 |
| 18.5.4. Classes of services | 663 |
| 18.5.5. Source emission of a <i>path</i> message | 668 |
| 18.5.6. Resv frame emission for guaranteed service | 669 |
| 18.5.7. Resv message emission for the controlled service | 672 |
| 18.5.8. The future of RSVP. | 673 |
| 18.6. Differentiated services | 675 |
| 18.7. Perspectives. | 677 |
| Bibliography | 679 |
| Index | 681 |